

D2 SERIES
SPDT SWITCH
DC-12.4 GHz ◆ **N, BNC, TNC**



The **D2 Series** features N, BNC or TNC connectors and a frequency range of DC to 12.4 GHz.

This series is available with fail-safe, latching self cut-off or pulse latching functions.

RF Impedance:	50 ohms nominal
Temperature Range:	-35°C to +85°C ambient
Operating Life:	1,000,000 cycles min.
Switching Time:	15 mSec max.
Switching Sequence:	Break Before Make
Environmental:	Designed in Accordance to MIL-DTL-3928 (Testing and Operation Modes)

SPECIFICATIONS

Frequency	VSWR (max.)	Insertion Loss (dB max.)	Isolation (dB min.)
DC-3 GHz	1.20	0.20	80
3-8 GHz	1.35	0.35	70
8-12.4 GHz	1.50	0.50	60

Actuator Current (typical)	12Vdc	15 Vdc	24 Vdc	28Vdc
Fail-safe	240mA	240mA	170mA	190mA
Latching	140mA	140mA	130mA	130mA

* If reduced coil current is required, please contact Factory.

AVAILABLE OPTIONS

OPTION 2 RF CONNECTORS	OPTION 4 VOLTAGE	OPTION 5 ACTUATOR	OPTION 6 FREQUENCY	OPTION 8 SPECIAL OPTIONS
1 - N 2 - BNC 3 - TNC	1 - 6 Vdc +/- 10% 2 - 12 Vdc +/- 10% 3 - 24-30 Vdc 4 - 48 Vdc +/- 10% 5 - 110 Vac +/- 10% 6 - 12-15 Vdc 7 - 18-20 Vdc 8 - 20-24 Vdc	Fail-safe A - Standard B - Indicators M - Diodes Q - Diodes, Indicators	2 - DC to 12.4 GHz	L - TTL (High) LL - TTL (Low) P - High Power Handling
OPTION 3 TERMINALS		Latching Self Cut-Off D - Diodes E - Diodes, Indicators	OPTION 7 POLARITY	
1 - Solder Terminals 2 - Circular Connector 4 - Sub M miniature D-Shell Connector		Pulse Latching C - Standard F - Indicators Y - Diodes L - Diodes, Indicators	0 - Not Applicable 8 - Positive Common 9 - Negative Common	
		Normally Open K - Standard H - Indicators J - Diodes G - Diodes, Indicators		

D2

-

2

Option 1
Series

Option 2
RF Connectors

Option 3
Terminals

Option 4
Voltage

Option 5
Actuator

Option 6
Frequency

Option 7
Polarity

Option 8
Special
Options